

HOW TO SET UP AND CARE FOR TROPHY & EXHIBIT CASE

ON ALL FREE STANDING (NON-WALL MOUNTED) CASES, INSTALL THE FURNITURE TIPPING RESTRAINT (HH500) PER INSTRUCTIONS LOCATED ON THE KIT'S PACKAGING.

1. Unpack case, doors, shelves and hardware from the skid.
2. Install the doors in case by lifting up into top track recess about 4" from left side. Move door in at bottom and lower edge of door into bottom track.
3. Clean thoroughly the glass area to receive door handles, placing them slightly below center, from top to bottom on left edge of inside door and right edge of outside door. Close each door fully into frame groove. Strip paper from handle and press handle firmly onto clean glass, using wood frame to align handle. To secure a good initial bond, open door and hold hand on inside face of glass behind handle pressing handle against glass with other hand.
4. Two half-length shelves may be positioned on common level using three brackets or one half-length shelf using two brackets. To secure bracket in standard, position in desired location and lock in place by tapping bracket down. Do not place bracket over standard screw as it may not lock in place.
5. Two plastic shelf rests must be used on each knife edge bracket to hold shelves, one with lip to rear against back, one with lip to front of bracket. Wide shelf rests are used only on center bracket if two half-length shelves are on a common level. Shorter rests are used on outside brackets (or on center brackets used to support a single shelf) turned wide face inward toward shelf center.
6. Level case in final position. Case is level when inside vertical edges of doors are parallel. Keep glass clean for best appearance.
7. There is a screw in the top door track that you unscrew slightly to lower screw head to block the doors from being lifted up and out. To remove doors you will have to reverse.